

BATTERIES

MOLL Dry



PRODUCT ADVANTAGES:

Sealed valve regulated battery

Carrying handles

Completely maintenance free

Very high reliability

Ideal for seasonal usage

Safe handling

Minimal self-discharging

High discharge ability and long life

Flexible employment for drive, current supply and also for starting

No acid leakage, no corrosion through acid fumes, especially suitable for indoor usage

Patented innercell connection

Special alloy and cycle-resistant active material

Special grid plate technology

AGM-technology with absorbed electrolyte, no free acid

TECHNICAL DATA

MOLL Dry		A	B	C	D
Rated voltage	V	12	12	12	12
Rated capacity at 27 °C					
C 100	Ah	45	60	70	95
C 10	Ah	34	50	55	67
C 5	Ah	32	45	50	60
Length	mm	211	246	278	353
Width	mm	175	175	175	175
Height	mm	175	190	190	190
Weight, filled approx.	kg	12.5	15.8	18.2	23.5

Type		Article numbers
A MOLL Dry	12 V, 45 Ah C 100	5200100005
B MOLL Dry	12 V, 60 Ah C 100	5200100006
C MOLL Dry	12 V, 70 Ah C 100	5200100010
D MOLL Dry	12 V, 95 Ah C 100	5200100029

Subject to modifications that represent progress.

03-2010